

(2) You must also conduct a directional survey that provides both inclination and azimuth, and digitally record the results in electronic format:

- (i) Within 500 feet of setting surface or intermediate casing;
- (ii) Within 500 feet of setting any liner; and
- (iii) When you reach total depth.

(b) *Survey requirements for directional well.* You must conduct directional surveys on each directional well and digitally record the results. Surveys must give both inclination and azimuth at intervals not to exceed 500 feet during the normal course of drilling. Intervals during angle-changing portions of the hole may not exceed 100 feet.

(c) *Measurement while drilling.* You may use measurement-while-drilling technology if it meets the requirements of this section.

(d) *Composite survey requirements.* (1) Your composite directional survey must show the interval from the bottom of the conductor casing to total depth. In the absence of conductor casing, the survey must show the interval from the bottom of the drive or structural casing to total depth; and

(2) You must correct all surveys to Universal-Transverse-Mercator-Grid-north or Lambert-Grid-north after making the magnetic-to-true-north correction. Surveys must show the magnetic and grid corrections used and include a listing of the directionally computed inclinations and azimuths.

(e) If you drill within 500 feet of an adjacent lease, the Regional Supervisor may require you to furnish a copy of the well's directional survey to the affected leaseholder. This could occur when the adjoining leaseholder requests a copy of the survey for the protection of correlative rights.

§ 250.462 What are the requirements for well-control drills?

You must conduct a weekly well-control drill with each drilling crew. Your drill must familiarize the crew with its roles and functions so that all crew members can perform their duties promptly and efficiently.

(a) *Well-control drill plan.* You must prepare a well control drill plan for each well. Your plan must outline the

assignments for each crew member and establish times to complete each portion of the drill. You must post a copy of the well control drill plan on the rig floor or bulletin board.

(b) *Timing of drills.* You must conduct each drill during a period of activity that minimizes the risk to drilling operations. The timing of your drills must cover a range of different operations, including drilling with a diverter, on-bottom drilling, and tripping.

(c) *Recordkeeping requirements.* For each drill, you must record the following in the driller's report:

- (1) The time to be ready to close the diverter or BOP system; and
- (2) The total time to complete the entire drill.

(d) *BSEE ordered drill.* A BSEE authorized representative may require you to conduct a well control drill during a BSEE inspection. The BSEE representative will consult with your on-site representative before requiring the drill.

§ 250.463 Who establishes field drilling rules?

(a) The District Manager may establish field drilling rules different from the requirements of this subpart when geological and engineering information shows that specific operating requirements are appropriate. You must comply with field drilling rules and non-conflicting requirements of this subpart. The District Manager may amend or cancel field drilling rules at any time.

(b) You may request the District Manager to establish, amend, or cancel field drilling rules.

APPLYING FOR A PERMIT TO MODIFY AND WELL RECORDS

§ 250.465 When must I submit an Application for Permit to Modify (APM) or an End of Operations Report to BSEE?

(a) You must submit an APM (form BSEE-0124) or an End of Operations Report (form BSEE-0125) and other materials to the Regional Supervisor as shown in the following table. You must also submit a public information copy of each form.